# **Standard Operating Procedures Paint Finishing and Detailing**

## **Headlight Lens Restoration Process**



#### Clean and Mask

Clean the damaged lens with soap and water. Perimeter mask the lens with two layers of masking tape.

## Sand to Remove Yellowing and Defects

Dry DA sand the damaged headlight lens with a 3 in. grade 500 3M™ Hookit™ Purple Clean Sanding Disc using a soft interface pad. Completely remove any yellowing and/or surface defects.

### 1st Step Scratch Refinement

Refine the grade 500 sand scratches by dry DA sanding with a 3 in. grade 800 3M<sup>™</sup> Hookit<sup>™</sup> Purple Clean Sanding Disc on a soft interface pad. Wipe the headlight lens clean.

#### 2nd Step Scratch Refinement

Refine the grade 800 sand scratches by DA sanding with a 3 in. grade 1000 3M™ Trizact™ Hookit™ Blending Disc on a soft interface pad. Use water to lubricate the grade 1000 foam abrasive disc. Spend extra time on this step to ensure removal of all grade 800 sand scratches. Wipe the headlight lens clean.

### 3rd Step Scratch Refinement

Refine the grade 1000 sand scratches by DA sanding with a 3 in. grade 3000 3M™ Trizact™ Hookit<sup>™</sup> Foam Disc on a soft interface pad. Use water to lubricate the grade 3000 foam abrasive disc. Spend extra time on this step to ensure removal of all grade 1000 sand scratches. Wipe the headlight lens clean.

#### Compound Lens

Completely remove the grade 3000 sand scratches using a 3 in. polisher with a 4 in. 3M<sup>™</sup> Perfect-It<sup>™</sup> Foam Compounding Pad and 3M™ Perfect-It™ EX AC Rubbing Compound. Wipe the headlight lens with a clean microfiber cloth.

#### Polish Lens

Polish the headlight lens using a 4 in. 3M<sup>™</sup> Perfect-It<sup>™</sup> Foam Polishing Pad and 3M™ Perfect-It™ EX Machine Polish. Wipe the headlight lens with a clean microfiber cloth. Remove the masking tape and inspect for quality.

Visit 3MCollision.com for more SOPs and videos

Note: For best results use a process dedicated microfiber cloth.

#### **Product List**

Meguiar's® Shampoo Plus, 1 gallon, PN D11101



Scotch® Performance Masking Tape 233+, 18mm x 55m (.75 in.), PN 26334



3M™ Hookit™ Soft Interface Pad, 3 in., PN 05771



3M™ Hookit™ Purple Clean Sanding Disc, 3 in., grade P500, PN 30272; 3 in., grade P800, PN 30260



3M™ Trizact™ Hookit™ Blending Disc, 3 in., grade P1000, PN 02091



3M™ Trizact™ Hookit™ Foam Disc, 3 in., 3000, PN 02087



3M™ Perfect-It™ EX AC Rubbing Compound, 8 oz., PN 36058



3M™ Perfect-It™ Foam Buffing Pad, 4 in., PN 30041

3M™ Perfect-It™ EX Machine Polish, 8 oz., PN 06093



3M™ Perfect-It™ Foam Polishing Pad, 4 in., PN 30042

3M™ Perfect-It™ Detail Cloth, PN 06016



### **Think About Your Health**

3M™ F-A-R™ Skull Screws™ Ear Plug, PN P1300



3M™ Half Facepiece Respirator, PN 07182



3M<sup>™</sup> Virtua<sup>™</sup> Protective Eyewear, PN 11326

## **Individual Product Instruction and Safety Information**

For individual product instructions and applicable precautions see product labels and associated literature for the individual product at **3MCollision.com** 

For product material safety data sheets see 3MCollision.com

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Automotive Aftermarket Division 3M Center, Building 223-6S-07 St. Paul, MN 55144-1000 U.S.A.

3M, Accuspray, Cubitron, E-A-R, Hookit, Perfect-It, Platinum, PPS, Roloc, Scotch, Scotchblok, Scotch-Brite, Skull Screws, SUN GUN, Trizact, Versaflo and Virtua are trademarks of 3M. All other trademarks are property of their respective owners.