

TRIM BLACK ULTRA

ultra | *adjective* | ul-tra | \ 'əl-trə \

1. going beyond what is usual or ordinary; extreme



BEFORE

COWL PANELS, WIPER ARMS



GRILLS



AFTER

MIRROR HOUSINGS



WINDOW TRIM



Trim Black Ultra is a true, jet-black trim paint formulated to match today's trim color and gloss levels. Designed for use on plastic, aluminum, steel, and stainless steel.

- Best-in-class appearance and sprayability
- True, jet-black color
- Adhesion to steel, aluminum, TPO and PP
- Sprays smooth for an OEM-like finish
- Three gloss levels to match a variety of OEM applications
- Reduces time and steps with superior coverage
- Ultra transfer efficiency aerosol

Part No.	Product	Size
49133	Trim Black Ultra - Matte	20 oz. Aerosol
49143	Trim Black Ultra - Satin	20 oz. Aerosol
49153	Trim Black Ultra - Gloss	20 oz. Aerosol



STEP 1 PREP

ALUMINUM, STEEL & STAINLESS STEEL

Clean surface with **SEM Solve** or **XXX Universal Surface Cleaner**. Sand surface with P400 grit sandpaper. Blow or wipe off dust and re-clean with **SEM Solve** or **XXX Universal Surface Cleaner**.

PLASTIC

Clean surface with **SEM Soap** and a gray scuff pad. Rinse with water and dry. Clean with **Plastic & Leather Prep**. If contamination still exists, water will bead on the surface. Repeat this step until beading no longer occurs.

To promote adhesion on ABS, PVC and other similar plastics, apply a medium wet coat of **Sand Free Adhesion Promoter**. Apply color while **Sand Free Adhesion Promoter** is still wet. As the **Sand Free Adhesion Promoter** evaporates, the color is drawn into the surface, creating excellent adhesion.

Due to the variety of substrates, it is recommended to test a small area before applying product. Full adhesion may take up to 48 hours.

STEP 2 APPLICATION

Agitate thoroughly! Shake can vigorously for one minute after mixing ball begins to rattle to ensure color uniformity and to prevent clogging. For best results, use when can temperature is approximately 70°F (21°C).

Coats: 1 – 2 medium wet

Flash Time: 3 – 5 minutes

Do not rush to reinstall the part. Adhesion of **Trim Black Ultra** improves with time. Full hardness is obtained in 48 hours.

RELATED PRODUCTS

Part	Product Name	Color	Container
38351	Plastic & Leather Prep		Gallon
38353	Plastic & Leather Prep		16 oz. Aerosol
38354	Plastic & Leather Prep		Cone Quart
38363	Sand Free Adhesion Promoter		16 oz. Aerosol
38364	Sand Free Adhesion Promoter		Cone Quart
38371	SEM Solve		Gallon
38373	SEM Solve		20 oz. Aerosol
38374	SEM Solve		Quart
39033	Trim Black Charcoal Metallic	Charcoal Metallic	16 oz. Aerosol
39063	Trim Black Gloss	Gloss Black	16 oz. Aerosol
39068	Trim Black Gloss	Gloss Black	Pint
39141	Trim Black	Black	Gallon
39143	Trim Black	Black	20 oz. Aerosol
39144	Trim Black	Black	Quart
39141-LV	Trim Black Low VOC	Black	Gallon
39144-LV	Trim Black Low VOC	Black	Quart
39362	SEM Soap		16 oz. Tube
39861	Plastic Adhesion Promoter		Gallon
39863	Plastic Adhesion Promoter		20 oz. Aerosol
39864	Plastic Adhesion Promoter		Cone Quart
77721	XXX Adhesion Promoter		Gallon
77723	XXX Adhesion Promoter		16 oz. Aerosol
77724	XXX Adhesion Promoter		Cone Quart
77763	XXX Universal Gun Cleaner		20 oz. Aerosol
77771	XXX Universal Surface Cleaner		Gallon
77774	XXX Universal Surface Cleaner		Quart



GET INFORMED

Visit our new website at semproducts.com

GET TRAINED

We have 14 new SOP videos to standardize your repair process

GET SOCIAL

Find us on Facebook, Instagram, YouTube and Twitter



SEM Products, Inc.
Rock Hill, SC 29730
1-800-831-1122
semproducts.com



Learn about Trim Black Ultra
semproducts.com/product/trim-black-ultra