

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 8/6/2019

Revision date: 6/10/2022 update 01/13/2023

Supersedes: 8/6/2019

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 2K Rapid Primer Filler Gray
Product code : 3680031 / REZ1145

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive refinish

1.3. Supplier

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON M5J 1T1

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Eye Irrit. 2A
Carc. 2
Repr. 2
STOT SE 3
Simple Asphy

2.2. GHS Label elements, including precautionary statements

GHS labeling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol
Contains gas under pressure; may explode if heated

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Precautionary statements (GHS)	<p>Causes serious eye irritation May cause drowsiness or dizziness Suspected of causing cancer Suspected of damaging fertility or the unborn child May displace oxygen and cause rapid suffocation</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center or doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p>
--------------------------------	--

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Butylene	CAS-No.: 115-10-6	30 – 60
Acetone	Acetone Dimethyl ketone / 2-Propanone / ACETONE / Propan-2-one / Propanone	CAS-No.: 67-64-1	7 – 13
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate / Butyl acetate, n- / Normal butyl acetate / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate / Acetato de n-butilo	CAS-No.: 123-86-4	7 – 13

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
2-Pentanone, 4-methyl-	2-Pentanone, 4-methyl- Hexone / Isobutyl methyl ketone / Isopropylacetone / Methyl isobutyl ketone / 4-Methyl-2-pentanone / 2-Methyl-4-pentanone / 4-Methylpentan-2-one / MIBK / Pentan-2-one, 4-methyl-	CAS-No.: 108-10-1	1 – 5
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene	CAS-No.: 1330-20-7	1 – 5
1-Butanol	1-Butanol n-Butyl alcohol / n-Butanol / Butanol, 1- / 1-Butyl alcohol / Butyl alcohol, n- / 1-Hydroxybutane / Butan-1-ol / Butanol, n- / N-BUTYL ALCOHOL / Normal butyl alcohol / Butyl alcohol / Butanol	CAS-No.: 71-36-3	1 – 5
2-Heptanone	2-Heptanone Methyl n-amyl ketone / n-Amyl methyl ketone / Amyl methyl ketone / Heptan-2-one / Methyl amyl ketone / Methyl pentyl ketone / Methyl n-pentyl ketone / METHYL AMYL KETONE	CAS-No.: 110-43-0	1 – 5
Propylene glycol monomethyl ether	Propylene glycol monomethyl ether Propylene glycol monomethyl ether / 2-Methoxy-1-methylethanol / 1-Methoxy-2-hydroxypropane / 1-Methoxypropan-2-ol / Propan-2-ol, 1-methoxy- / Propylene glycol 1-methyl ether / Propylene glycol methyl ether / Methoxyisopropanol / 1-Methoxy-2-propanol / 1-Methoxypropanol-2 / METHOXYISOPROPANOL / 2-Propylene glycol 1-monomethyl ether / Methyl proxitol / Monomethyl ether of propyleneglycol / Monomethyl ether of propylene glycol	CAS-No.: 107-98-2	1 – 5
Ethylbenzene	Ethylbenzene Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	0.1-1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of causing cancer. Suspected of damaging the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media : Do not use water spray.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. vapors may form explosive mixture with air.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Use water spray to keep fire-exposed containers cool. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). vapors are heavier than air and may spread along floors.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2K Rapid Primer Filler Gray	
No additional information available	
Dimethyl ether (115-10-6)	
No additional information available	
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	250 ppm
ACGIH OEL STEL [ppm]	500 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	2500 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	590 mg/m ³
NIOSH REL TWA [ppm]	250 ppm

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

n-Butyl acetate (123-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butyl acetate
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2020
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	1700 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	710 mg/m ³
NIOSH REL TWA [ppm]	150 ppm
NIOSH REL (STEL)	950 mg/m ³
NIOSH REL STEL [ppm]	200 ppm
2-Pentanone, 4-methyl- (108-10-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone
ACGIH OEL TWA [ppm]	20 ppm
ACGIH OEL STEL [ppm]	75 ppm
Remark (ACGIH)	TLV® Basis: URT irr; dizziness; headache. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	METHYL ISOBUTYL KETONE
BEI (BLV)	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2021
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	500 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	205 mg/m ³
NIOSH REL TWA [ppm]	50 ppm
NIOSH REL (STEL)	300 mg/m ³
NIOSH REL STEL [ppm]	75 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
1-Butanol (71-36-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	1400 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (Ceiling)	150 mg/m ³
NIOSH REL C [ppm]	50 ppm
US-NIOSH chemical category	Potential for dermal absorption
2-Heptanone (110-43-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	50 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	800 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	465 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
Propylene glycol monomethyl ether (107-98-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol
ACGIH OEL TWA [ppm]	50 ppm
ACGIH OEL STEL [ppm]	100 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	360 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL (STEL)	540 mg/m ³
NIOSH REL STEL [ppm]	150 ppm
Ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	0.15 g/g Kreatinin Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	435 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL (STEL)	545 mg/m ³
NIOSH REL STEL [ppm]	125 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Wear suitable gloves
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Gray
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (-0.4 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Extremely flammable aerosol.

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.9375 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
Longitud de proyección de la llama	: >75cm - < 100cm
Escena retrospectiva	: Possible

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Dimethyl ether (115-10-6)	
LC50 inhalation rat	164000 ppm/4h
ATE CA (Gases (except aerosol dispensers and lighters))	164000 ppmV/4h

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	50100 mg/m ³ (Exposure time: 8 h)
ATE CA (oral)	5800 mg/kg body weight
ATE CA (vapors)	50.1 mg/l/4h
ATE CA (dust,mist)	50.1 mg/l/4h
n-Butyl acetate (123-86-4)	
LD50 oral rat	10768 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat	0.74 mg/l/4h
ATE CA (oral)	10768 mg/kg body weight
2-Pentanone, 4-methyl- (108-10-1)	
LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat	11.6 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 inhalation rat	2000 – 4000 ppm/4h
ATE CA (oral)	2080 mg/kg body weight
ATE CA (Dermal)	3000 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	2000 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rat	1100 mg/kg
ATE CA (oral)	3500 mg/kg body weight
ATE CA (Dermal)	1100 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
1-Butanol (71-36-3)	
LD50 oral rat	700 mg/kg
LD50 dermal rabbit	3402 mg/kg
LC50 inhalation rat	> 8000 ppm/4h
ATE CA (oral)	700 mg/kg body weight

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

1-Butanol (71-36-3)	
ATE CA (Dermal)	3400 mg/kg body weight
2-Heptanone (110-43-0)	
LD50 oral rat	1600 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	10300 mg/kg
LC50 inhalation rat	> 16.7 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))
LC50 inhalation rat	2000 – 4000 ppm (Exposure time: 6 h)
ATE CA (oral)	1600 mg/kg body weight
ATE CA (Dermal)	10300 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	2000 ppmV/4h
ATE CA (vapors)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Propylene glycol monomethyl ether (107-98-2)	
LD50 oral rat	5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	13 g/kg
LC50 inhalation rat	> 7559 ppm (Exposure time: 6 h)
ATE CA (oral)	5000 mg/kg body weight
ATE CA (Dermal)	13000 mg/kg body weight
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg body weight
ATE CA (Dermal)	15400 mg/kg body weight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmV/4h
ATE CA (vapors)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
2-Pentanone, 4-methyl- (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-Pentanone, 4-methyl- (108-10-1)	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
n-Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
2-Pentanone, 4-methyl- (108-10-1)	
STOT-single exposure	May cause respiratory irritation.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.
1-Butanol (71-36-3)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
Propylene glycol monomethyl ether (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.
	: Not classified
STOT-repeated exposure	
2-Pentanone, 4-methyl- (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapor, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
1-Butanol (71-36-3)	
LOAEL (oral, rat, 90 days)	500 mg/kg body weight Animal: rat
NOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Propylene glycol monomethyl ether (107-98-2)	
LOAEL (oral,rat,90 days)	2757 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (oral,rat,90 days)	919 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Ethylbenzene (100-41-4)	
NOAEL (oral,rat,90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

2K Rapid Primer Filler Gray	
Vaporizer	Aerosol

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna

Acetone (67-64-1)	
LC50 - Fish [1]	4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

n-Butyl acetate (123-86-4)	
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-Pentanone, 4-methyl- (108-10-1)	
LC50 - Fish [1]	505 mg/l
EC50 - Crustacea [1]	1250 mg/l
NOEC chronic fish	57 mg/l
NOEC chronic crustacea	7.8 mg/l
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
1-Butanol (71-36-3)	
LC50 - Fish [1]	1730 – 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [2]	1897 – 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	4.1 mg/l
2-Heptanone (110-43-0)	
LC50 - Fish [1]	126 – 137 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	> 90.1 mg/l Test organisms (species): Daphnia magna
Propylene glycol monomethyl ether (107-98-2)	
LC50 - Fish [1]	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea: Acartia tonsa
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l

12.2. Persistence and degradability

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2K Rapid Primer Filler Gray	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
2K Rapid Primer Filler Gray	
Bioaccumulative potential	Not established.
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18
Acetone (67-64-1)	
BCF - Fish [1]	0.69
Partition coefficient n-octanol/water	-0.24
n-Butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1.81 (at 23 °C)
2-Pentanone, 4-methyl- (108-10-1)	
Partition coefficient n-octanol/water	1.19
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15
1-Butanol (71-36-3)	
BCF - Fish [1]	0.64
Partition coefficient n-octanol/water	0.785 (at 25 °C)
2-Heptanone (110-43-0)	
Partition coefficient n-octanol/water	1.98
Propylene glycol monomethyl ether (107-98-2)	
BCF - Fish [1]	< 2
Partition coefficient n-octanol/water	-0.437
Ethylbenzene (100-41-4)	
BCF - Fish [1]	15
Partition coefficient n-octanol/water	3.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1950
UN-No. (TDG) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : LTD QTY
Hazard labels (DOT) : LTD QTY



TDG

Transport hazard class(es) (TDG) : 2.1
Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT
UN-No.(DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG
UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Methyl isobutyl ketone which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date : 08/06/2019
Revision date : 06/10/2022
Other information : None.

2K Rapid Primer Filler Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Prepared by

: Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-phrases	
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Simple Asphy	Simple Asphyxiant
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Indication of changes:
SDS update.

SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.